

# **ODS-AGM16B** (PC535)

### Technical Data Sheet

#### **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

#### **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	14Ah
Capacity (10-hour rate)	13Ah
Cold Cranking Amps (CCA, SAE J537)	200A
PHCA - 5-second pulse current	535A
HCA	300A
MCA	265A
Reserve capacity	21 mins
Short circuit current (using IEC method)	1000A
Internal resistance at 20°C (using IEC method)	8 mΩ

#### **Dimensions & Weight**

Length	170 mm
Width	99 mm
Height (to top of terminals)	157 mm
Height Container	157 mm
Weight	5.4 kg

#### **Temperature**

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

### **Charging & self-discharge**


Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

#### Fitting, handling & storage


Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).


ODY ACID 18

# Terminal Position




## Terminal Type









PDF Generated at https://eu.odysseybattery.com 08/03/2022 12:50:52 Information correct at time of exporting PDF. Please check website for updates.

