

# ODX-AGM34 78 (34/78-PC1500)

**Technical Data Sheet** 

## **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

## **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	68Ah
Capacity (10-hour rate)	62Ah
Cold Cranking Amps (CCA, SAE J537)	850A
PHCA - 5-second pulse current	1500A
HCA	1250A
MCA	1050A
Reserve capacity	135 mins
Short circuit current (using IEC method)	3100A
Internal resistance at 20°C (using IEC method)	2.5 mΩ

## **Dimensions & Weight**

Length	277 mm	
Width	173 mm	
Height (to top of terminals)	201 mm	
Height Container	185 mm	
Weight	22.5 kg	

## **Temperature**

Operating Temperature Range	-40°C to +80°C
Optimum Storage Temperature	+20°C

## **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

## Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

## Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 08/03/2022 12:31:32 Information correct at time of exporting PDF. Please check website for updates.



Solutions


EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug. Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780



## **Terminal Position**



## **Terminal Type**


SAE Terr	ninals	Side Terminal
mm±0.2	15.6 mm±0.2 m±0.2	3/8-16 THREA 0.34" DEEP
sitive	Negative	28.5mm

17.2

19.3

Pos









LEFT POSITIVE DUAL TERMINALS E & SIDE)