

Range: **EMERGENCY AGM**
 Type name: **TBE6-7**
 Barcode: **8436594880667**



PERFORMANCES*		CONFIGURATION	
Voltage:	6 V	Size:	150x34x94 mm
Capacity:	7,2 Ah (20h)	Polarity:	6
Cap. 5/10/100h:	6,1/6,7/8 Ah	Terminal:	F2 (faston)
Energy at 100h:	0,05 kWh	Holddown:	-
Cycles at 50%:	500	Ventilation:	Valve regulated (VRLA)
Max. current:	108 A (5seg)	Maintenance:	Not required (MF)
Int. Resistance:	12 mΩ		
Self-Discharge:	15 months		
(from the date of production, at 25°C)			

*According to standards IEC 60254/60896

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	Manufacturer-sealed AGM	Container:	ABS/black
Alloy:	Calcium	Lid:	ABS/black
Separator:	AGM (glass mat)	Plugs:	Termal sealing, ABS/black
Total Weight:	1,2 kg	Handles:	-
Origin:	Asia		

RECOMMENDATIONS	
Storage:	Check voltage every 8 months.
Recharge:	Use automatic chargers with constant voltage and AGM setup.
Installation:	Use the appropriate cable section and length. Keep connections tight.

CEMA Baterías is the exclusive importer for Europe of DECK Battery products

TABLES & CHARTS

EMERGENCY AGM

TBE6-7

