

**MONBAT Premium SMF A78L3X0\_1 80 Ah**

According to EN 50342



**Premium**

SEALED MAINTENANCE FREE



**Electrical specification**

<b>Voltage:</b>	<b>12V</b>
<b>Capacity:</b>	<b>80 Ah</b>
<b>Cold cranking current:</b>	<b>760 A [EN]</b>
<b>Cold cranking current:</b>	<b>460 A [DIN]</b>

**Mechanical specification**

<b>Dimensional group:</b>	<b>L3</b>
<b>ETN reference:</b>	<b>580 043 076 SMF</b>
<b>DIN reference:</b>	<b>-</b>
<b>Dimensions (LxWxH):</b>	<b>278x175x190</b>
<b>Cell Layout:</b>	<b>0</b>
<b>Terminal Type:</b>	<b>1</b>

**Container**

<b>Case</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Bottom hold-down</b>	<b>B13</b>
	<b>Colour</b>	<b>Black</b>

<b>Lid</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Cover design</b>	<b>SMF</b>
	<b>Colour</b>	<b>Black</b>

<b>Vent caps</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Type</b>	<b>SMF</b>
	<b>Colour</b>	<b>Black</b>

<b>Handles</b>	<b>Material</b>	<b>Polypropylene</b>
	<b>Position</b>	<b>Top - on lid</b>
	<b>Colour</b>	<b>Black</b>


**Battery classification as per EN 50342-6**

<b>Water consumption</b>	<b>Charge retention</b>	<b>Vibration resistance</b>	<b>Endurance Level</b>
<b>W4</b>	<b>C2</b>	<b>V2</b>	<b>E2</b>


**Weight**

<b>Battery weight:</b>	<b>12.90</b>
<b>Acid weight:</b>	<b>5.60</b>
<b>Total battery weight:</b>	<b>18.50</b>

**Layout**



**Hold-down**



**Separator**

<b>Type</b>	<b>PE</b>
-------------	-----------