

Range: **MONOBLOCK**
 Type name: **OZX165.A**
 Barcode: **8436594880797**



3	-	1

PERFORMANCES*		CONFIGURATION	
Voltage:	12 V	Size:	513x190x223 mm (A)
Capacity:	165 Ah (100h)	Polarity:	3
Cap. 10/20h:	140/150 Ah	Terminal:	1 (taper)
Energy at 100h:	2 kWh	Holddown:	-
Cicles at 50%:	50	Ventilation:	Individual plugs
PV Cicles (24%):	200	Maintenance:	Very low maintenance
Self-Discharge:	12 months		
(from the date of production, at 25°C)			

*According to standards IEC 60896/61427

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	Punched, with regular surface	Container:	PP/black
Alloy:	Calcium	Lid:	Flat, PP/black
Separator:	PE envelope	Plugs:	Screw, PP/black
Total Weight:	32,7 kg	Handles:	On container, rope/black
Origin:	Europe		

RECOMENDATIONS	
Storage:	Check voltage every 6 months. Avoid exposure to sub-zero temperatures.
Recharge:	Use automatic chargers with constant voltage.
Installation:	Use the appropriate cable section and length. Keep connections tight.

TABLES & CHARTS

MONOBLOCK

OZX165.A

OZX165.A BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge rate	C5 (5h)	C10 (10h)	C20 (20h)	C100 (100h)
End of discharge voltage	10,20 V	10,50 V	10,50 V	10,80 V
Discharge capacity	120 Ah	140 Ah	145 Ah	165 Ah

