


Range: **AGM BLOCK**
 Type name: **OZX195AGM**
 Barcode: **8436594881008**



PERFORMANCES*		CONFIGURATION	
Voltage:	12 V	Size:	518x273x240 mm (C)
Capacity:	195 Ah (100h)	Polarity:	3
Cap. 10/20h:	165/180 Ah	Terminal:	1 (taper)
Energy at 100h:	2,3 kWh	Holddown:	-
Cicles at 50%:	500	Ventilation	Valve regulated
PV Cicles (24%):	1000	Maintenance:	Not required (MF)
Self-Discharge:	12 months		
(from the date of production, at 25°C)			

*According to standards IEC 60896/61427

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	AGM	Container:	PP/white
Alloy:	Calcium	Lid:	Flat double, PP/black
Separator:	AGM	Plugs:	Termal sealing, PP/black
Total Weight:	56,2 kg	Handles:	On container, rope/black
Origin:	Europe		

RECOMENDATIONS	
Storage:	Check voltage every 8 months. Avoid exposure to sub-zero temperatures.
Recharge:	Use automatic chargers with constant voltage.
Installation:	Use the apropiate cable section and length. Keep connections tight.

TABLES & CHARTS

AGM BLOCK

OZX195AGM

OZX195AGM BATTERY DISCHARGE PERFORMANCE AT 25°C

Discharge rate	C5 (5h)	C10 (10h)	C20 (20h)	C100 (100h)
End of discharge voltage	10,20 V	10,50 V	10,50 V	10,80 V
Discharge capacity	145 Ah	165 Ah	180 Ah	195 Ah

